

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
3 October 2002 (03.10.2002)

PCT

(10) International Publication Number
WO 02/076284 A2

(51) International Patent Classification⁷: **A61B** 10/068,264 5 February 2002 (05.02.2002) US
10/090,968 5 March 2002 (05.03.2002) US

(21) International Application Number: PCT/US02/08805

(22) International Filing Date: 22 March 2002 (22.03.2002) (71) Applicant: **VIACOR, INC.** [US/US]: 66 H Concord Street, Wilmington, MA 01887 (US).

(25) Filing Language: English

(26) Publication Language: English

(72) Inventors: **COHN, William, E.**: 104 Lagrange Street, Chestnut Hill, MA 02467 (US). **LIDDICOAT, John, R.**: Barberry Farm, Barberry Road, Sewickley, PA 15143 (US). **STREETER, Richard, B.**: 66 Brookside Avenue, Winchester, MA 01890 (US). **TAYLOR, Daniel, C.**: 35 Fanueil Street, Brighton, MA 02135 (US). **WOOLFSON, Steven, B.**: 85 East India Row, Apt. 39G, Boston, MA 02110-3394 (US).

(30) Priority Data:


60/278.153	23 March 2001 (23.03.2001)	US
60/279.974	29 March 2001 (29.03.2001)	US
60/279.973	29 March 2001 (29.03.2001)	US
60/280.038	30 March 2001 (30.03.2001)	US
60/283.820	13 April 2001 (13.04.2001)	US
60/312.217	14 August 2001 (14.08.2001)	US
60/339.481	26 October 2001 (26.10.2001)	US
60/348.424	14 January 2002 (14.01.2002)	US
10/068.700	5 February 2002 (05.02.2002)	US

(74) Agent: **PANDISCIO, Mark, J.**: Pandiscio & Pandiscio, 470 Totten Pond Road, Waltham, MA 02451-1914 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU.

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR REDUCING MITRAL REGURGITATION



(57) Abstract: Apparatus for reducing mitral regurgitation, by applying a force to the wall of the coronary sinus so as to force the posterior leaflet anteriorly and thereby reduce mitral regurgitation.

WO 02/076284 A2

Best Available Copy



CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK,
SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,
NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report

- (84) **Designated States (regional):** ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

METHOD AND APPARATUS FOR REDUCING MITRAL REGURGITATIONReference To Pending Prior Patent Applications

This patent application:

(1) is a continuation-in-part of pending prior U.S. Patent Application Serial No. 10/068,264, filed 02/05/02 by Daniel C. Taylor et al. for METHOD AND APPARATUS FOR IMPROVING MITRAL VALVE FUNCTION

(Attorney's Docket No. VIA-29);

(2) is a continuation-in-part of pending prior U.S. Patent Application Serial No. 10/068,700, filed 02/05/02 by William E. Cohn et al. for APPARATUS AND METHOD FOR REDUCING MITRAL REGURGITATION (Attorney's Docket No. VIA-16);

(3) is a continuation-in-part of pending prior U.S. Patent Application Serial No. 10/090,968, filed 03/05/02 by William E. Cohn et al. for APPARATUS AND METHOD FOR REDUCING MITRAL REGURGITATION (Attorney's Docket No. VIA-17);

(4) claims benefit of pending prior U.S. Provisional Patent Application Serial No. 60/278,153, filed 03/23/01 by William E. Cohn et al. for METHOD AND

- 2 -

APPPARATUS TO IMPROVE MITRAL VALVE FUNCTION (Attorney's Docket No. VIA-18 PROV);

(5) claims benefit of pending prior U.S. Provisional Patent Application Serial No. 60/279,974, filed 03/29/01 by Daniel C. Taylor et al. for METHOD AND APPARATUS TO IMPROVE MITRAL VALVE FUNCTION (Attorney's Docket No. VIA-19 PROV);

(6) claims benefit of pending prior U.S. Provisional Patent Application Serial No. 60/280,038, filed 03/30/01 by William E. Cohn et al. for METHODS AND APPARATUS FOR TEMPORARY IMPROVEMENT IN MITRAL VALVE FUNCTION (Attorney's Docket No. VIA-20 PROV);

(7) claims benefit of pending prior U.S. Provisional Patent Application Serial No. 60/279,973, filed 03/29/01 by Daniel C. Taylor et al. for METHODS AND DEVICES TO IMPROVE MITRAL VALVE FUNCTION (Attorney's Docket No. VIA-21 PROV);

(8) claims benefit of pending prior U.S. Provisional Patent Application Serial No. 60/283,820, filed 04/13/01 by William E. Cohn et al. for METHOD AND APPARATUS FOR TEMPORARY IMPROVEMENT IN MITRAL VALVE FUNCTION (Attorney's Docket No. VIA-22 PROV);

- 3 -

(9) claims benefit of pending prior U.S. Provisional Patent Application Serial No. 60/312,217, filed 08/14/01 by Daniel C. Taylor et al. for METHOD AND APPARATUS FOR TEMPORARY IMPROVEMENT IN MITRAL VALVE FUNCTION (Attorney's Docket No. VIA-23 PROV);

(10) claims benefit of pending prior U.S. Provisional Patent Application Serial No. 60/339,481, filed 10/26/01 by William E. Cohn et al. for TRANSVASCULAR APPROACH TO MITRAL VALVE PROCEDURES (Attorney's Docket No. VIA-30 PROV); and

(11) claims benefit of pending prior U.S. Provisional Patent Application Serial No. 60/348,424, filed 01/14/02 by Daniel C. Taylor et al. for METHOD AND APPARATUS TO IMPROVE MITRAL VALVE FUNCTION (Attorney's Docket No. VIA-31 PROV).

The aforementioned eleven (11) patent applications are hereby incorporated herein by reference.

Field Of The Invention

This invention relates to surgical methods and apparatus in general, and more particularly to surgical methods and apparatus for improving mitral valve function.

- 4 -

Background Of The Invention

Mitral valve repair is the procedure of choice to correct mitral regurgitation of all etiologies. With the use of current surgical techniques, between 70% and 95% of regurgitant mitral valves can be repaired. The advantages of mitral valve repair over mitral valve replacement are well documented. These include better preservation of cardiac function and reduced risk of anticoagulant-related hemorrhage, thromboembolism and endocarditis.

In current practice, mitral valve surgery requires an extremely invasive approach that includes a chest wall incision, cardiopulmonary bypass, cardiac and pulmonary arrest, and an incision on the heart itself to gain access to the mitral valve. Such a procedure is associated with high morbidity and mortality. Due to the risks associated with this procedure, many of the sickest patients are denied the potential benefits of surgical correction of mitral regurgitation. In addition, patients with moderate, symptomatic mitral regurgitation are denied early intervention and undergo

- 5 -

surgical correction only after the development of cardiac dysfunction.

Mitral regurgitation is a common occurrence in patients with heart failure and a source of important morbidity and mortality in these patients. Mitral regurgitation in patients with heart failure is caused by changes in the geometric configurations of the left ventricle, papillary muscles and mitral annulus. These geometric alterations result in mitral leaflet tethering and incomplete coaptation at systole. In this situation, mitral regurgitation is corrected by plicating the mitral valve annulus, either by (i) sutures alone or by (ii) sutures in combination with a support ring, so as to reduce the circumference of the distended annulus and restore the original geometry of the mitral valve annulus.

More particularly, current surgical practice for mitral valve repair generally requires that the posterior mitral valve annulus be reduced in radius by surgically opening the left atrium and then fixing sutures, or sutures in combination with a support ring, to the internal surface of the annulus; this structure is used to pull the annulus back into a smaller radius,

- 6 -

thereby reducing mitral regurgitation by improving leaflet coaptation.

This method of mitral valve repair, generally termed "annuloplasty", effectively reduces mitral regurgitation in heart failure patients. This, in turn, reduces symptoms of heart failure, improves quality of life and increases longevity. Unfortunately, however, the invasive nature of mitral valve surgery and the attendant risks render most heart failure patients poor surgical candidates. Thus, a less invasive means to increase leaflet coaptation and thereby reduce mitral regurgitation in heart failure patients would make this therapy available to a much greater percentage of patients.

Mitral regurgitation also occurs in approximately 20% of patients suffering acute myocardial infarction. In addition, mitral regurgitation is the primary cause of cardiogenic shock in approximately 10% of patients who develop severe hemodynamic instability in the setting of acute myocardial infarction. Patients with mitral regurgitation and cardiogenic shock have about a 50% hospital mortality. Elimination of mitral regurgitation in these patients would be of significant

- 7 -

benefit. Unfortunately, however, patients with acute mitral regurgitation complicating acute myocardial infarction are particularly high-risk surgical candidates, and are therefore not good candidates for a traditional annuloplasty procedure. Thus, a minimally invasive means to effect a temporary reduction or elimination of mitral regurgitation in these critically ill patients would afford them the time to recover from the myocardial infarction or other acute life-threatening events and make them better candidates for medical, interventional or surgical therapy.

A less invasive means to reduce mitral regurgitation would also be an attractive alternative for patients needing to undergo any of the following procedures: (a) isolated mitral valve repair, (b) multiple valve procedures, (c) mitral repair and coronary artery bypass, (d) mitral valve repair and other surgical procedure, or (e) mitral valve repair and an interventional cardiac procedure.

Summary Of The Invention

As a result, one object of the present invention is to provide a method and apparatus for treating

- 8 -

mitral regurgitation which does not suffer from the disadvantages associated with conventional annuloplasty.

Another object of the present invention is to provide a method and apparatus for treating mitral regurgitation which can be deployed either permanently (e.g., for patients suffering from heart failure) or temporarily (e.g., for patients suffering from mitral regurgitation with acute myocardial infarction).

Another object of the present invention is to provide a minimally invasive method and apparatus for the repair of heart valves to improve their function.

Another object of the present invention is to provide a method and apparatus for the repair of the mitral valve that eliminates the need for cardiopulmonary bypass and/or cardiac arrest and/or general anesthesia.

Another object of the present invention is to provide a method and apparatus for the repair of the mitral valve that facilitates the use of smaller incisions.

Another object of the present invention is to provide a method and apparatus to effect a change in

- 9 -

the geometry of the annulus of the mitral valve that increases mitral leaflet coaptation and reduces mitral valve regurgitation.

Another object of the present invention is to provide a method and apparatus to effect a change in the geometry of the left atrium that increases mitral leaflet coaptation and reduces mitral regurgitation.

Another object of the present invention is to provide an apparatus that is anchored partially or wholly outside the coronary sinus such that tension can be created between the proximal and distal anchored points so as to move these two points closer together and thereby effect a favorable change in the geometry of the mitral valve annulus.

Another object of the present invention is to provide an apparatus that is anchored partially or wholly outside the coronary sinus such that tension can be created between the proximal and distal anchored points so as to move these two points closer together and thereby effect a favorable change in left atrial geometry, with minimal, if any, trauma to the blood vessel.

- 10 -

Another object of the present invention is to provide a method and apparatus to alter the geometry of the mitral valve annulus such that (1) the distance between the anterior and posterior mitral leaflets is shortened; and (2) the coronary sinus assumes a more straight course.

Another object of the present invention is to provide a method and apparatus to alter left atrial geometry such that (1) the distance between the anterior and posterior mitral leaflets is shortened; and (2) the coronary sinus assumes a more straight course.

Another object of the present invention is to provide a method and apparatus for altering the geometry of the mitral valve annulus in an adjustable and/or reversible fashion such that the effect on mitral valve function can be adjusted so as to achieve the best possible result.

Another object of the present invention is to provide a method and apparatus for altering left atrial geometry in an adjustable and/or reversible fashion such that the effect on mitral valve function can be adjusted so as to achieve the best possible result.

- 11 -

Another object of the present invention is to provide an apparatus that is anchored partially or wholly outside the coronary sinus such that a greater geometric change in the left atrium can be created (that in turn increases mitral leaflet coaptation and reduces mitral regurgitation) when compared to anchoring only within the coronary sinus.

These and other objects are addressed by the present invention, which is made possible by the discovery that the mitral annulus may be remodeled without the plication of conventional, open-surgery annuloplasty.

The present invention comprises a method and apparatus for increasing mitral leaflet coaptation without direct surgical exposure of the mitral valve via the left atrium. More particularly, the present invention comprises a method and apparatus for effecting a geometric, conformational or dimensional alteration in the annulus of the mitral valve by manipulating cardiac structures external to the left atrium and, in so doing, improving mitral valve function.

- 12 -

In a preferred embodiment, the present invention utilizes access obtained in part via the coronary sinus. The coronary sinus is the largest vein of the heart. During a large portion of its course in the atrioventricular groove, the coronary sinus lies directly beneath the endocardium of the left atrium and adjacent to the posterior annulus of the mitral valve. An apparatus appropriately placed into the coronary sinus will be in direct apposition to the left atrium and the posterior annulus of the mitral valve. Manipulation of such apparatus may be used to effect a geometric change in the left atrium, and hence the annulus of the mitral valve, in order to increase mitral leaflet coaptation. Preferably, the apparatus is adjustable so that its effect may be varied, at the time of the initial procedure or at a later date, so as to achieve the best possible result.

In one preferred form of the invention, the apparatus comprises a distal anchor, a proximal anchor and a flexible filament extending therebetween. By setting the distal anchor distally, near the end of the coronary sinus, and setting the proximal anchor proximally, near the mouth of the coronary sinus, and

- 13 -

thereafter adjustably cinching the filament between the two anchors, the geometry of the coronary sinus, and hence the geometry of the left atrium and the mitral valve, may be adjusted so as to improve mitral leaflet coaptation. The effects of this left atrial conformational change include (1) decreasing the distance between the anterior and posterior leaflets of the mitral valve; (2) straightening the posterior mitral valve annulus; and (3) decreasing the distance between the fibrous trigones of the heart by altering the shape of the mitral valve annulus.

Access to perform this procedure may be obtained either percutaneously via any vessel in the body or via a chamber of the heart, such as the right atrium. The latter approach may involve a chest wall incision or a thoracoscopic approach. Visualization of the procedure may be obtained by fluoroscopy, echocardiography, intravascular ultrasound, angioscopy, or real-time magnetic resonance imaging. It is anticipated that assessment of the efficacy of the procedure will be obtained with echocardiography, although other imaging modalities may also be suitable.

Brief Description Of The Drawings

The above and other objects and features of the present invention will be more fully disclosed or rendered obvious by the following detailed description of the preferred embodiments of the invention, which is to be considered together with the accompanying drawings wherein like numbers refer to like parts and further wherein:

Fig. 1 is a schematic view of portions of the human vascular system;

Fig. 2 is a schematic view of portions of the human heart;

Fig. 3 is a schematic view showing one embodiment of apparatus formed in accordance with the present invention;

Figs. 4-10 are a series of views illustrating use of the system of Fig. 3 to reduce mitral regurgitation;

Fig. 11 is a schematic view showing another embodiment of apparatus formed in accordance with the present invention; and

- 15 -

Fig. 12 is a schematic view showing still another embodiment of apparatus formed in accordance with the present invention.

Detailed Description Of The Preferred Embodiments

The coronary sinus is the largest vein in the human heart. During a large portion of its course in the atrioventricular groove, the coronary sinus typically extends adjacent to the left atrium of the heart for a distance of approximately 5 to 10 centimeters. Significantly, for a portion of its length, e.g., typically approximately 7-9 cm, the coronary sinus extends substantially adjacent to the posterior perimeter of the mitral annulus. The present invention takes advantage of this fact. More particularly, by deploying an appropriate apparatus in the coronary sinus, adjacent to the posterior leaflet of the mitral valve, pressure may be brought to bear on the posterior annulus of the mitral valve, whereby to move the posterior annulus anteriorly so as to improve leaflet coaptation and, as a result, reduce mitral regurgitation. In this respect it should be appreciated that the posterior annulus may be shifted

- 16 -

anteriorly so as to achieve, or to attempt to achieve to the extent anatomically possible, leaflet-to-leaflet engagement or leaflet-to-annulus engagement (e.g., where a leaflet may be tethered due to left ventricular distortion). Both of these types of engagement, or targeted engagement, are intended to be encompassed by the terms "improved leaflet coaptation" and/or "increased leaflet coaptation" and the like.

In one preferred embodiment of the invention, access to the coronary sinus is gained percutaneously, e.g., the apparatus is introduced into the patient's vascular system via the jugular vein or via the left subclavian vein, passed down the superior vena cava, passed through the right atrium and then passed into the coronary sinus, where it is deployed. Alternatively, the apparatus may be introduced into the coronary sinus through a small incision in the heart, or through some other incision into the patient's vascular system.

Once deployed, the apparatus may be left in position permanently (e.g., in the case of patients suffering from mitral regurgitation associated with

- 17 -

heart failure) or the elongated body may be left in position only temporarily (e.g., in the case of patients suffering from mitral regurgitation associated with acute myocardial infarction).

Visualization of the procedure may be obtained by fluoroscopy, echocardiography, intravascular ultrasound, angiography, real-time magnetic resonance imaging, etc. The efficacy of the procedure may be determined through echocardiography, although other imaging modalities may also be suitable.

Looking now at Figs. 1 and 2, there are shown aspects of the cardiovascular system 3 of a patient. More particularly, cardiovascular system 3 generally comprises the heart 6, the superior vena cava 9, the right subclavian vein 12, the left subclavian vein 15, the jugular vein 18, and the inferior vena cava 21. Superior vena cava 9 and inferior vena cava 21 communicate with the heart's right atrium 24. The coronary ostium 27 leads to coronary sinus 30. At the far end 31 (Fig. 2) of coronary sinus 30, the vascular structure turns into the vertically-descending anterior interventricular vein ("AIV") 32 (Fig. 1). For purposes of the present invention, it can generally be

- 18 -

convenient to consider the term "coronary sinus" to mean the vascular structure extending between coronary ostium 27 and AIV 32.

As seen in Fig. 2, between coronary ostium 27 and AIV 32, coronary sinus 30 generally extends substantially adjacent to the posterior perimeter of the annulus 33 of the mitral valve 36. Mitral valve 36 comprises a posterior leaflet 39 and an anterior leaflet 42. In the case of a regurgitant mitral valve, posterior leaflet 39 and anterior leaflet 42 will generally fail to properly coapt at systole, thereby leaving an intervening gap 45 which will permit regurgitation.

Looking next at Fig. 3, there is shown a system 100 which comprises one preferred embodiment of the present invention. More particularly, system 100 generally comprises a guidewire 103, a cinching device 106 and a delivery cannula 109.

Guidewire 103 comprises a flexible body 112 having a distal end 115 and a proximal end 118. The distal end 115 of guidewire 103 preferably includes a sharp tip 121 for allowing the distal end of guidewire 106 to penetrate tissue.

- 19 -

Cinching device 106 comprises a flexible body or filament 124 having a distal end 127 and a proximal end 130. In the case where central lumen 136 extends from distal end 127 to proximal end 130, central lumen 136 would preferably collapse on itself when guidewire 103 is removed or a portion of guidewire 103 would remain within central lumen 136 to prevent blood from the right atrium from bleeding into the pericardial space 51. See Fig. 4. A distal anchor 139 is disposed at the distal end 127 of flexible body 124 and is preferably constructed from or covered with a material which promotes blood clotting to seal the hole created by the tip of guidewire 106 and distal end 127 of flexible body 124. A proximal anchor 142 is disposed at the proximal end 130 of flexible body 124. Proximal anchor 142 preferably comprises a plurality of radial projections 145 formed on flexible body 124 and a head 146 having a central opening 147 therein. Head 146 is intended to "ratchet" over radial projections 145 so as to be adjustable along flexible body 124. More particularly, by ratcheting head 146 distally or proximally along radial projections 145, the length of filament extending between distal anchor 139 and

- 20 -

proximal anchor 142 may be shortened or lengthened as desired. Head 146 also includes one or more holes H for permitting blood to flow past head 146 when the cinching device is deployed in the body.

Delivery catheter 109 comprises a flexible body 148 having a distal end 151 and a proximal end 154. A central lumen 157 extends down the length of flexible body 148.

System 100 may be used as follows to reduce mitral regurgitation.

First, using devices and method currently well known to interventional cardiologists any commercially available delivery catheter is passed down the jugular vein 18 (or the left subclavian vein 15) of a patient, down superior vena cava 9, through right atrium 24 of the heart, and then into coronary sinus 30. When the tip of the commercially available delivery catheter is located at or near the entrance of the AIV, guidewire 103 is passed down the center of catheter 109. It will be appreciated that as the commercially available delivery catheter and flexible guidewire 103 are passed down coronary sinus 30, the catheter and guidewire will tend to assume the natural curved shape of the coronary

- 21 -

sinus, due to the flexible nature of the catheter and guidewire. Then the guidewire's sharp tip 121 is pushed through the end wall 31 of the coronary sinus, across the intervening tissue 48 and into pericardial space 51 and the commercially available delivery catheter is removed leaving the flexible guidewire 103 in place. See Fig. 4.

Next, cinching device 106 and delivery catheter 109 are passed down over the guidewire 103 until the distal end of the delivery catheter is positioned in coronary sinus 30. See Fig. 5. More particularly, cinching device 106, with its distal anchor 139 and head 146 of proximal anchor 142 in folded back positions, is loaded into the interior lumen 157 of delivery catheter 109, and then the assembly is fit over guidewire 103, with guidewire 103 being received in central lumen 136 of cinching device 106. Cinching device 106 and delivery catheter 109 are passed down guidewire 103, together, in this position. Again, it will be appreciated that as the cinching device 106 and flexible delivery catheter 109 pass down the coronary sinus, the cinching device and delivery catheter will tend to assume the natural curved shape of the coronary

- 22 -

sinus, due to the flexible natures of the cinching device and the delivery catheter.

Then, with the distal end 151 of delivery catheter 109 positioned at the far end 31 of the coronary sinus, the distal end of cinching device 106 is advanced forward, through intervening tissue 48, until it enters pericardial space 51. See Fig. 6. At this point the distal anchor 139 of cinching device 106 deploys. See Fig. 7.

Next, delivery catheter 109 is withdrawn proximally until it's distal end is disposed proximally of the cinching device's proximal anchor 142, whereupon head 146 of the proximal anchor 142 will unfold. See Fig. 8.

Next, the cinching device's head 146 is advanced distally, over ratcheting projections 145, until head 146 engages the coronary ostium 27. Then the proximal end of flexible body 124 is withdrawn proximally, causing the distance between distal anchor 139 and proximal anchor 142 to be reduced, whereby to cause at least a portion of coronary sinus 30 to assume a more straight configuration adjacent to the posterior annulus of mitral valve 36. See Fig. 9. This action

- 23 -

causes the posterior annulus of mitral valve 36 to be forced anteriorly, whereby the mitral valve's posterior leaflet 39 will also move anteriorly so as to improve mitral valve leaflet coaptation and thereby reduce (or completely eliminate) mitral valve regurgitation. In this respect it should be appreciated that the posterior annulus may be shifted anteriorly so as to achieve, or to attempt to achieve to the extent anatomically possible, leaflet-to-leaflet engagement or leaflet-to-annulus engagement (e.g., where a leaflet may be tethered due to left ventricular distortion). Both of these types of engagement, or targeted engagement, are intended to be encompassed by the terms "improved leaflet coaptation" and/or "increased leaflet coaptation" and the like. Using standard visualization means (e.g. echocardiography or fluoroscopy), the degree of cinching is adjusted (i.e., either tighter or looser) so as to reduce (or completely eliminate) regurgitation in mitral valve 36.

It should be appreciated that when the cinching device's head 146 is in engagement with coronary ostium 27, blood will be free to flow into the coronary ostium due to the presence of holes H in head 146.

- 24 -

At this point the cinching device 106 is locked in position.

System 100 is left in this position until it is no longer needed. In some cases this may mean that system 100 is left in position for a period of a few hours, days or weeks; in other cases system 100 may be substantially permanent. If system 100 is to be left in position, the proximal end of flexible body 124 may be cut away and removed. See Fig. 10. This may be done with an instrument advanced down delivery catheter 109. Then delivery catheter 109 is removed from the patient.

Thus it will be seen that with the present invention, cinching device 106 is positioned in the normally curved portion of the coronary sinus adjacent to the mitral valve's posterior leaflet, with its distal anchor 139 located in pericardial space 51 and its proximal anchor 142 located at the coronary ostium 27. By properly cinching the length of filament 124 between these two anchors, cinching device 106 will cause at least a portion of the coronary sinus to assume a more straight configuration adjacent to the posterior leaflet of the mitral valve. This action

- 25 -

will in turn drive the posterior annulus of the mitral valve anteriorly, so as to improve leaflet coaptation and thereby reduce mitral regurgitation. Thus, by inserting the cinching device 106 into the coronary sinus adjacent to the posterior leaflet of the mitral valve and thereafter cinching it down as appropriate, the annulus of the mitral valve is effectively manipulated so that it will assume an increased radius of curvature.

It has also been found that by inserting the cinching device into the coronary sinus adjacent to the posterior leaflet of the mitral valve, the left ventricle may also be remodeled so as to help alleviate congestive heart failure.

In an alternative embodiment of the invention, the delivery catheter 109 is itself guided into coronary sinus 30 without the use of guidewire 103, and the distal end of cinching device 103 is used to open a path through intervening tissue 48 and into pericardial space 51. In this form of the invention, guidewire 103 may be omitted entirely, and the central lumen 136 in cinching device 106 may also be omitted. However, the distal end of cinching device 106 preferably has a

- 26 -

trocar device to help open a path through intervening tissue 48. See, for example, Fig. 11, where system 100 is shown comprising cinching device 106 and delivery catheter 109, and further wherein cinching device 106 comprises a distal trocar 160 to open a path through intervening tissue 48 and into pericardial space 51.

And in another alternative embodiment of the invention, the cinching device's distal anchor 139 and/or its proximal anchor 142 may be replaced with an inflatable balloon anchor. In this case delivery catheter 109 may be adapted so that it is itself guided into coronary sinus 30 without the use of guidewire 103, and the central lumen 136 of cinching device 106 may be used as an inflation lumen. See, for example, Fig. 12, where system 100 is shown comprising cinching device 106 and delivery catheter 109, and further wherein cinching device 106 comprises a distal anchor 139 comprising an inflatable balloon and a distal trocar 160 to open a path through intervening tissue 48 and into pericardial space 51. Central lumen 136 allows fluid to be delivered to and removed from the inflatable balloon, whereby to inflate or deflate the balloon on command.

- 27 -

In the procedures described above, the distal end of cinching device 106 (and, depending on the embodiment, the distal end of guidewire 103) is described as penetrating all the way through the intervening tissue 48 and into pericardial space 51, so that the distal anchor 139 can be set into pericardial space 51 and bear against the exterior of intervening tissue 48. This arrangement is generally preferred, since it allows greater separation between distal anchor 139 and proximal anchor 142, and since it allows a strong anchoring arrangement highly resistant to slippage. However, if desired, it is also possible to set distal anchor 139 into the interior of intervening tissue 51.

Similarly, in the procedures described above, the proximal anchor 142 is described as being set against coronary ostium 27. Again, this arrangement is generally preferred since it allows good anchor separation and it allows a strong anchoring arrangement highly resistant to slippage. However, if desired, it is also possible to set proximal anchor 142 at other locations.

- 28 -

The procedures described above relate to effecting changes in left atrial geometry using access obtained via the coronary sinus or other cardiac vein. Such procedures might also be performed using access obtained via the circumflex coronary artery. In addition, a similar approach could be used to perform procedures on the tricuspid valve.

It will be understood that the particular devices and methods embodying the invention are shown by way of illustration only and not as limitations of the invention. The principles and features of this invention may be employed in various and numerous embodiments without departing from the scope of the invention.

- 29 -

What Is Claimed Is:

1. Apparatus for reducing mitral regurgitation, said apparatus comprising:

a cinching device comprising a distal anchor, a proximal anchor and a flexible body extending therebetween, said distal anchor being adapted to be positioned distal to the distal end of the coronary sinus and the proximal anchor being adapted to be positioned at the coronary ostium, with the flexible body extending through said coronary sinus between said distal anchor and said proximal anchor, and further wherein at least one of said distal anchor and said proximal anchor is configured for ratcheting action relative to said flexible body, whereby the length of body between said distal anchor and said proximal anchor may be reduced,

whereby when said distal anchor is positioned distal to said distal end of said coronary sinus and said proximal anchor is positioned at said coronary ostium, with the flexible body extending through said coronary sinus between said distal anchor and said

- 30 -

proximal anchor, and said body is thereafter cinched so as to reduce the length of body between said distal anchor and said proximal anchor, a force may be exerted on the posterior annulus so as to reduce mitral regurgitation.

2. Apparatus according to claim 1 wherein said distal anchor is adapted to be set in the pericardial space adjacent to the distal end of the coronary sinus.

3. Apparatus according to claim 1 wherein said distal anchor is adapted to be set in the intervening tissue located between the pericardial space and the distal end of the coronary sinus.

4. Apparatus according to claim 1 wherein said proximal anchor comprises a plurality of radial projections formed on said filament and a head having a central opening therein, the size and construction of said radial projections and said central opening being coordinated so as to enable a ratcheting action between said filament and said head.

- 31 -

5. Apparatus according to claim 4 wherein said head has a plurality of additional openings therein so as to pass blood therethrough.

6. Apparatus according to claim 1 wherein said system further comprises a delivery catheter sized to receive said cinching device.

7. Apparatus according to claim 1 wherein said system further comprises a guidewire and a delivery catheter.

8. Apparatus according to claim 7 wherein said cinching device comprises a central lumen for receiving said guidewire therein.

9. Apparatus according to claim 1 wherein said system further comprises a delivery catheter sized to receive said cinching device, and further wherein said cinching device comprises a sharp tip at its distal end, distal to said distal anchor.

- 32 -

10. Apparatus according to claim 1 wherein said distal anchor comprises an inflatable balloon.

11. A method for reducing mitral regurgitation, said method comprising the steps of:

providing a cinching device comprising a distal anchor, a proximal anchor and a flexible body extending therebetween, said distal anchor being adapted to be positioned distal to the distal end of the coronary sinus and the proximal anchor being adapted to be positioned at the coronary ostium, with the flexible body extending through said coronary sinus between said distal anchor and said proximal anchor, and further wherein at least one of said distal anchor and said proximal anchor is configured for ratcheting action relative to said flexible body, whereby the length of body between said distal anchor and said proximal anchor may be reduced;

positioning said distal anchor distal to said distal end of said coronary sinus and positioning said proximal anchor at said coronary ostium, with the flexible body extending through said coronary sinus

- 33 -

between said distal anchor and said proximal anchor;
and

cinching said body so as to reduce the length of
body between said distal anchor and said proximal
anchor, whereby a force may be exerted on the posterior
annulus so as to reduce mitral regurgitation.

12. A method according to claim 11 wherein said
distal anchor is set in the pericardial space adjacent
to the distal end of the coronary sinus.

13. A method according to claim 11 wherein said
distal anchor is set in the intervening tissue located
between the pericardial space and the distal end of the
coronary sinus.

14. A method according to claim 11 wherein said
proximal anchor comprises a plurality of radial
projections formed on said body and a head having a
central opening therein, the size and construction of
said radial projections and said opening being
coordinated so as to enable a ratcheting action between
said body and said head, and further wherein cinching

- 34 -

said body is achieved by moving said head relative to said body.

15. A method according to claim 14 wherein said head has a plurality of openings therein so as to pass blood therethrough.

16. A method according to claim 11 wherein said cinching device is carried to the coronary sinus inside a delivery catheter.

17. A method according to claim 11 wherein said cinching device is carried to the coronary sinus over a guidewire.

18. Apparatus according to claim 1 wherein said distal anchor has an external surface which promotes blood clotting.

19. Apparatus according to claim 8 wherein said central lumen collapses upon itself to prevent blood leakage from one chamber to another.

- 35 -

20. A method according to claim 11 wherein said distal anchor is set through the myocardium tissue and into the left ventricular adjacent to the distal end of the coronary sinus.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6

**FIG. 7**




FIG. 8




FIG. 9





FIG. 10






FIG. 12

THIS PAGE BLANK (USPTO)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
3 October 2002 (03.10.2002)

PCT


(10) International Publication Number
WO 02/076284 A3

- (51) International Patent Classification: **A61F 2/24** 10/068,264 5 February 2002 (05.02.2002) US
10/090,968 5 March 2002 (05.03.2002) US
- (21) International Application Number: PCT/US02/08805
- (22) International Filing Date: 22 March 2002 (22.03.2002) (71) Applicant: **VIACOR, INC.** [US/US]; 66 H Concord Street, Wilmington, MA 01887 (US).
- (25) Filing Language: English (72) Inventors: **COHN, William, E.**; 104 Lagrange Street, Chestnut Hill, MA 02467 (US). **LIDDICOAT, John, R.**; Barberry Farm, Barberry Road, Sewickley, PA 15143 (US). **STREETER, Richard, B.**; 66 Brookside Avenue, Winchester, MA 01890 (US). **TAYLOR, Daniel, C.**; 35 Fanueil Street, Brighton, MA 02135 (US). **WOOLFSON, Steven, B.**; 85 East India Row, Apt. 39G, Boston, MA 02110-3394 (US).
- (26) Publication Language: English (74) Agent: **PANDISCIO, Mark, J.**; Pandiscio & Pandiscio, 470 Totten Pond Road, Waltham, MA 02451-1914 (US).
- (30) Priority Data:
- | | | |
|------------|------------------------------|----|
| 60/278,153 | 23 March 2001 (23.03.2001) | US |
| 60/279,974 | 29 March 2001 (29.03.2001) | US |
| 60/279,975 | 29 March 2001 (29.03.2001) | US |
| 60/280,038 | 30 March 2001 (30.03.2001) | US |
| 60/283,820 | 13 April 2001 (13.04.2001) | US |
| 60/312,217 | 14 August 2001 (14.08.2001) | US |
| 60/339,481 | 26 October 2001 (26.10.2001) | US |
| 60/348,424 | 14 January 2002 (14.01.2002) | US |
| 10/068,700 | 5 February 2002 (05.02.2002) | US |
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU.

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR REDUCING MITRAL REGURGITATION

(57) Abstract: Apparatus (100) for reducing mitral regurgitation, by applying a force to the wall of the coronary sinus (30) so as to force the posterior leaflet (39) anteriorly and thereby reduce mitral regurgitation.



WO 02/076284 A3



CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK,
SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,
NE, SN, TD, TG).

Published:

— with international search report

- (84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent

- (88) **Date of publication of the international search report:**
27 February 2003

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US02/08805

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : A61F 2/24

US CL : 623/2.36

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : Please See Continuation Sheet

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
Please See Continuation Sheet

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X ---	US 5,269,809 A (Hayhurst et al) 14 December 1993, Figs. 2, 6-8, 11-12B.	1,4,6,9,18 -----
Y		7,8,11-20
X ---	US 4,669,473 A (Richards et al) 2 June 1987, Figs. 8-10, 11, 15.	1,4,6,9,18 -----
Y		2,3,5,10
Y, P	US 6,210,432 A (Solem et al) 3 April 2001, see entire document.	7,8,11-20
Y	US 5,720,726 A (Marcadis et al) 24 February 1998, Figs. 13-15, col. 9, lines 55-61.	10

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

Special categories of cited documents:	
* "A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention.
"E" earlier application or patent published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

10 July 2002 (10.07.2002)

Date of mailing of the international search report

12 DEC 2002

Name and mailing address of the ISA/US

Commissioner of Patents and Trademarks

Box PCT

Washington, D.C. 20231

Facsimile No. (703)305-3230

Authorized officer

Corrine McDermott

Telephone No. 703-308-0858

Form PCT/ISA/210 (second sheet) (July 1998)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US02/08805

Continuation of B. FIELDS SEARCHED Item 1:
623/2.36, 2.37; 606/220, 232, 151, 153

Continuation of B. FIELDS SEARCHED Item 3:
EAST
search terms: valve, leakage, failure, dysfunction, flexible, adjustable, tighten, implant

Form PCT/ISA/210 (second sheet) (July 1998)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

THIS PAGE BLANK (USPTO)